



Coaxial Cable Siamese Plenum Rated

RG59/U 95% BC BRD +
18/2 WHITE CMP SECURITAS

SES TYPE HS

243300352 (1000bx) 243300752 (500rl)



1.0 Construction

1.1 Conductor

- 1.1.1 Material: Bare Copper
- 1.1.2 Size: 20
- 1.1.3 Conductors:
- 1.1.4 Construction: Solid

1.2 Insulation

- 1.2.1 Material: FEP
- 1.2.2 Color Code: N/A

1.3 Jacket

- 1.3.1 Material: LSPVC
- 1.3.2 OD: 0.360 X 0.194 Inches nom.
- 1.3.2 Color: White

1.4 Shield

- 1.4.1 Material: CU Braid
- 1.4.2 Coverage: 95%
- 1.4.2 Drain AWG Size:

1.5 Electrical Properties

- 1.5.1 Temperature: N/R
- 1.5.2 Voltage: 300 Volts
- 1.5.3 Capacitance: 17.8 pF/Ft. nom.
- 1.5.4 Impedance: 75 Ohms/M'
- 1.5.5 Velocity of Propagation: 82%
- 1.5.6 DC Resistance: 10.1 Ohms/M'
@ 20C

1.6 Put-Ups

- 1.6.1 Length: 1000' & 500'
- 1.6.2 Package: Box/Reel
- 1.6.3 Weight: 48 lbs/1,000'

Compliance:

- UL 13
- UL 444
- UL 910
- NEC Article 725
- NEC Article 800

The information and specifications described herein are subject to error or omission and to change without notice.

Paige provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Paige be liable for any damages (including consequential, indirect, incidental, special, punitive or exemplary damages) whatsoever, even if Paige has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

We want to hear from you!

P.O. Box 368, Union, NJ 07083

Tel: 888.423.8947 info@paigeelectric.com

www.paigedatacom.com

