

# **GameChanger Cable**

Unshielded Twisted Pair Plenum Rated - CMP

258300336 46224PPBLW (legacy part no)

US Patent No. 10,453,589



# 1.0 Scope

1.1 This cable consists of 4 pair solid bare copper; color-coded FEP insulation; overall LSFR-PVC jacket. RoHS-2 Compliant

#### 2.0 Construction

#### 2.1 Conductor

2.1.1 Material: Bare Copper

2.1.2 Construction: Solid 22 AWG

#### 2.2 Insulation

2.1.1 Material: Ultra Low-Loss Dielectric

2.1.2 O.D.: 0.044" nom

2.1.3 Color Code

Pair 1: White/Blue

Blue

Pair 2: White/Orange

Orange

Pair 3: White/Green

Croor

Pair 4: White/Brown

Brown

## 2.3 Core Assembly:

2.3.1 4 twisted pairs cabled together to form the main core.

#### 2.4 Jacket

2.4.1 Material: LSFR-PVC

2.4.2 OD: 0.248"nom

2.4.3 Color: Blue with a white stripe

2.4.4 Ripcord under jacket

2.4.5 Markings: "PAIGE GAMECHANGER

PATENT NO. 10,453,589 (UL) CMP --- C(UL) FT6 EXXXXX ROHS SUN RES" (Ascending/Descending length marking)

# 2.5 Electrical Properties

2.5.1 Conductor Resistance: ≤6.35Ω/100m

2.5.2 Insulation Resistance: ≥5000MΩKm

(DC500V Charged 1 Min)

2.5.3 Voltage Endurance: DC 1500V/min

2.5.4 Mutual Capacitance: ≤7.0nF/100m

2.5.5 Core-Core Resistance Unbalance: ≤5%

## 2.6 Temperature Rating

2.6.1 -20°C to +75°C

# 2.7 Power over Ethernet Support

2.7.1 Class 1 - 8

# 3.0 Weights and Dimensions

#### 3.1 Put Up

3.1.1 Length: 1,000 ft box

3.1.2 Weight: 32 lbs

3.1.3 Dimensions: 15" x 12" x 15"



200 Sheffield St, Suite 302, Mountainside, NJ 07092

Tel: 888.423.8947 gamechanger@paigeelectric.com



<b>Frequency</b> MHz	<b>Return Loss</b> ≥dB/100m	<b>Insertion Loss</b> ≤dB/100m	<b>NEXT</b> ≥dB/100m	<b>PSNEXT</b> ≥dB/100m
1	24	1.5	90	87
10	31	4.8	75	72
20	32	7.0	64	61
100	26	16.1	50	47
200	24	23.2	48	45
250	21	26.1	47	44
350	20	31.4	45	42
500	19	38.3	43	40
550	18	40.4	42	39

<sup>\*</sup>Values above 250 MHz are for engineering information only

# **Application**

GameChanger cabling is designed specifically for transmitting Ethernet and can support all 8 classes of Power over Ethernet.

Maximum transmission distance exceeds Category Rating limits, but varies with equipment and settings used. If you have any questions about the maximum recommended distance for a particular installation, please contact us.

### Connectors

GameChanger cabling works with most Cat 6 jacks and patch cords, but is only recommended to work with Platinum Tools ezEX44 or ezEX48 RJ45 modular plugs.

## **Alternate Constructions**

GameChanger cabling is also available with:

- 258310333 Riser, Yellow w/ White Stripe
- 258300336 Plenum, Blue w/ White Stripe
- 258300310 Plenum, White
- 258330804 OSP, Black
- 258340804 OSP Shielded, Black
- 258802404 Class I, Division 1 Armored

# **Frequently Asked Questions**

For FAQ and best practices please visit: www.paigedatacom.com/gamechanger

We want to hear from you!

200 Sheffield St, Suite 302, Mountainside, NJ 07092

Tel: 888.423.8947 gamechanger@paigeelectric.com www.paigedatacom.com/gamechanger

