



GameChanger Cable

Unshielded Twisted Pair
C_{ca}-s1a, d0, a1

258502336 500m drum

258500336 305m box



1.0 Scope

1.1 This cable consists of 4 pair solid bare copper; color-coded PE insulation; overall LSZH-FRPE jacket. EN50575:2014 C_{ca}-s1a, d0, a1 and CE/ RoHS-2 Compliant

2.0 Construction

2.1 Conductor

- 2.1.1 Material: Bare Copper
- 2.1.2 Construction: Solid 22AWG
- 2.1.3 O.D.: 0.610 mm min.

2.2 Insulation

- 2.2.1 Material: Ultra Low-Loss Dielectric
- 2.2.2 O.D.: 1.1176 mm nom.
- 2.2.3 Color Code
 - Pair 1: White/Blue + Blue
 - Pair 2: White/Orange + Orange
 - Pair 3: White/Green + Green
 - Pair 4: White/Brown + Brown

2.3 Core Assembly:

- 2.3.1 4 twisted pairs stranded together to form the main core.

2.4 Jacket

- 2.4.1 Material: LSZH-FRPE with UV Resistance

2.4.2 OD: 6.2992 mm nom.

2.4.3 Color: Blue with White Stripe

2.4.4 Ripcord under jacket

2.4.5 Markings: "PAIGE(R)
GAMECHANGER PATENT
PENDING 22 AWG EN50575:2014
CE Cca-s1b,d1,a1 RoHSXXXXXX
(Ascending/ Descending
length marking)

2.5 Electrical Properties

- 2.5.1 Conductor Resistance:
≤9.38Ω/100m
- 2.5.2 Insulation Resistance:
≥5000MΩKm
(DC500V Charged 1 Min)
- 2.5.3 Voltage Endurance: DC 1500V/min
- 2.5.4 Mutual Capacitance: ≤7.0nF/100m
- 2.5.5 Core-Core Resistance
Unbalance: ≤5%

2.6 Temperature Rating

- 2.6.1 -20°C to +75°C (installation)
- 2.6.2 -40°C to +75°C (operating)

2.7 Power over Ethernet Support

- 2.7.1 Class 1 - 8

We want to hear from you!

P.O. Box 368, Union, NJ 07083

Tel: 888.423.8947 gamechanger@paigeelectric.com

www.paigedatacom.com/gamechanger



Frequency MHz	Return Loss ≥dB/100m	Attenuation ≤dB/100m	NEXT ≥dB/100m	PSNEXT ≥dB/100m
1	32.7	1.5	82.0	78.5
4	34.4	3.0	71.3	66.8
10	30.5	4.8	63.6	60.3
16	33.5	6.2	56.7	56.2
20	35.0	6.2	56.7	56.2
25	34.1	7.8	59.3	55.3
31.25	31.5	8.8	60.9	56.9
62.50	31.1	8.8	60.9	56.9
100	29.4	16.3	50.2	49.2

Application

GameChanger cabling is designed specifically for transmitting Ethernet and can support all 8 classes of Power over Ethernet.

Maximum transmission distance exceeds Category Rating limits, but varies with equipment and settings used. If you have any questions about the maximum recommended distance for a particular installation, please contact us.

Connectors

GameChanger cabling works with most Category 6 non shielded connectors. Make sure your connector supports 22AWG conductors.

Alternate Constructions

GameChanger cabling is also available with:

- 258330804 - OSP, Black
- 258340804 - OSP Shielded, Black

Frequently Asked Questions

For FAQ and best practices please visit:
www.paigedatacom.com/gamechanger

Regional Availability

United Kingdom, Europe, Middle East

We want to hear from you!

Tel: 888.423.8947 gamechanger@paigeelectric.com
www.paigedatacom.com/gamechanger

