



# GameChanger Hazardous Location Cable

ITC-HL C1/D1

258802404



## 1.0 Scope

1.1 This cable consists of 4 pair solid bare copper; color-coded Fluorinated Ethylene Propylene (FEP) insulation; inner FEP and PVC jacket, Continuously Corrugated Welded (CCW) Armor and outer PVC jacket. RoHS-2 Compliant, Sunlight Resistant, Direct Burial. Suitable for Class 1 Div 1, Class 2 Div 1 and Class 2 Div 2 installations  
UL2250 Listed Type ITC 300V  
UL2225 Listed Type ITC-HL 300V for use in Class 1 Div 1 Hazardous locations.

## 2.0 Construction

- 2.1 Conductor
  - 2.1.1 Material: Bare Copper
  - 2.1.2 Construction: Solid
- 2.2 Insulation
  - 2.2.1 Material: FEP
  - 2.2.3 O.D.: 0.0425" nom
  - 2.2.4 Color Code
    - Pair 1: White/Blue  
Blue
    - Pair 2: White/Orange  
Orange
    - Pair 3: White/Green  
Green
    - Pair 4: White/Brown

Brown

- 2.3 Core Assembly:
  - 2.3.1 4 twisted pairs cabled together to form the main core which is then jacketed with FEP and PVC inner jackets.
- 2.4 Jackets
  - 2.4.1 Material: FEP/PVC/PVC
  - 2.4.2 Inner Wall Thickness 1: 0.0218" nom
  - 2.4.3 Inner Wall Thickness 2: 0.568" nom.
  - 2.4.4 Outer OD: 0.95" nom.
  - 2.4.5 Color: Black
  - 2.4.6 Corrugated Aluminum Armor Between Jackets.
  - 2.4.7 Markings: PAIGE GAMECHANGER CABLE™ PATENT # 10,453,589 22 AWG 4 Pair (UL) Type ITC-HL Sun Res ROHS (Ascending/Descending length marking)
- 2.5 Electrical Properties
  - 2.5.1 Conductor Resistance:  $\leq 9.38\Omega/100m$
  - 2.5.2 Max DC Resistance Unbalance:  $\leq 5\%$
  - 2.5.3 Nominal Velocity of Propagation 68%

We want to hear from you!  
200 Sheffield St, Mountainside, NJ 07092

Tel: 888.423.8947 [gamechanger@paigeelectric.com](mailto:gamechanger@paigeelectric.com)  
[www.paigeelectric.com/gamechanger](http://www.paigeelectric.com/gamechanger)



Frequency MHz	Return Loss ≥dB/100m	Attenuation ≤dB/100m	NEXT ≥dB/100m	PSNEXT ≥dB/100m
1	28	1.5	77	75
4	31	3.0	68	66
10	33	4.8	62	60
16	33	6.2	59	57
20	33	6.2	58	56
25	32	7.8	56	54
31.25	31	8.8	55	53
62.50	29	8.8	50	48
100	28	16.3	47	45

### Application

GameChanger cabling is designed specifically for transmitting Power over Ethernet and IP video and control traffic. Any use other use is not covered under the warranty.

Maximum transmission distance exceeds Category Rating limits, but varies with equipment and settings used. If you have any questions about the maximum recommended distance for a particular installation, please contact us.

### Connectors

GameChanger cabling works with most Category 6 connectors. For best results, Paige recommends Platinum Tools ezEX connectors.

### Alternate Constructions

GameChanger cabling is also available with:

- 258300336 - Plenum, Blue w/ White Stripe
- 258300310 - Plenum, White
- 258330804 - OSP (non shielded), Black
- 258340804 - OSP (Shielded), Black
- 258900804 - Class 1 D2 Black

### Frequently Asked Questions

For FAQ and best practices please visit:  
[www.paigedatacom.com/gamechanger](http://www.paigedatacom.com/gamechanger)

**We want to hear from you!**

P.O. Box 368, Union, NJ 07083

Tel: 888.423.8947 [gamechanger@paigeelectric.com](mailto:gamechanger@paigeelectric.com)

[www.paigeelectric.com/gamechanger](http://www.paigeelectric.com/gamechanger)

